

PRODUCT SPECIFICATION

GlassIIEdge™

FOLD 'SLIDE'™
SYSTEMS

Window & Door Innovation Since 2001



Welcome

FSDC Global is a UK, CA and USA based independently owned and operated business specialising in the design, manufacture and distribution of folding sliding (bifold) doors worldwide since 2001.

Manufactured to our customer's exact specifications, our doors and windows are available in the largest combination of materials in the industry and an array of designs, to suit both traditional and contemporary tastes.

We pride ourselves on offering Folding Sliding / Doors and windows which include specialist features within the standard price. This includes the slim sight lines to ensure minimal visual obstruction and maximum light for aesthetic appeal; finger safe gaskets which prevent any injury from trapped fingers, top and bottom or both running systems, a large range of materials, glazing options and seals which all offer exceptional thermal values and superb energy efficiency levels which meet all building regulations.

Our own hardware brand (Fold'N'Slide) is uniquely designed and accredited, independently tested and approved. Fold'N'Slide hardware is accepted as one of the only universally compatible folding sliding door running systems in the marketplace; whether manufacturing timber, aluminum or vinyl folding sliding doors you will find the Fold'N'Slide hardware range offers you limitless opportunities.

We specialise in a number of products in wood, aluminium, PVCu / Vinyl, aluminium with wood and our patented GlassEdge™ technology. These products include Folding Patio Doors and Windows (Bi-folding), Centre Folding Doors, Sliding Doors, Sliding Stacking Doors, Glass walls, Movable Walls, Operable Walls and Room Dividers. All make it possible for us to provide a complete solution for home renovation, improvement or new build projects, as well as commercial requirements.

From humble beginnings FSDC Global has now established itself as a leading design and manufacturer of Bi-fold doors (glass patios, glass walls, concertina doors) internationally.

Paul Shearman

Group CEO



Mission statement

Our commitment to continuous improvement and meeting the needs of clients is unwavering and infectious. In particular, we have always ensured that our manufacturing processes are conducted, taking into account the preservation of the environment and the efficient and cost effective management of waste.

We only make folding sliding doors, it is what we do, nobody does it better than us!

- FSDC Global want our products and business to be regarded as the worldwide benchmark for innovation, quality and excellence in service, against which all others will be measured
- FSDC Global want everyone to aspire to bring the outside into their homes, with a folding sliding door
- FSDC Global will continue to prove that excellence in design doesn't have to cost the earth
- FSDC Global will enable all clients to achieve their aspirations, at a surprisingly affordable price
- FSDC Global want our customers, suppliers and employees, to share in our passion for folding sliding doors
- FSDC Global will continue to extend the credibility of our products and services by effective management of our impact on the environment, through the implementation of rigorous Responsible Purchasing and Waste Management Policies, with the ultimate aim of achieving Zero Waste to Landfill
- FSDC Global strongly uphold our belief in the philosophy of "excellence in everything", by way of our commitment to continuous improvement of the product and the business
- FSDC Global always aim to exceed the expectations of our clients and competitors, with regards to design features, quality and service delivery
- No matter how large FSDC Global become, we will work hard to retain the core values of a small family business, which have been at the heart of our achievements thus far, encouraging individuals to be personally committed to sharing in our success
- The FSDC Global will continue to uphold our commitment to serving the community by way of active job creation and training, within our local vicinity, to promote growth and prosperity within the local economy

Jack of one trade, master of one

Choice Custom made to suit your design, available in impact and non impact Aluminum, Wood, Wood Clad Aluminum and Vinyl

Function Inward, Outward, Right and Left, opening to suit you

Security Fully tested 5 point locking system complete with incorporated security design features

Durable Using our own roller design, **FOLD 'n' SLIDE™**
SYSTEMS HARDWARE
Fold'n'Slide hardware keeps the door running smooth

Things we consider **important**

Weatherproof Fully tested to ASTM standards

Efficient low thermal values, to keep you warm in the cold & cool in the heat

Tested A Florida Building Code approved impact product, NFRC

Aesthetics Perfectly balanced profiles, giving maximum strength with minimum frame

Quality Every purpose made part is designed by European engineers, and the doors are built by hand

Confidence We pride ourselves on making one product well, and specialize in it

Warranty 10 years complete peace of mind



Specification overview

Company overview

FSDC

You are buying from a specialist manufacturer (we ONLY manufacture folding sliding doors)	✓
International shipping service	✓
Company formed in 2001, over 18 years trading (residential & commercial customers)	✓
Quick Turn-a-Round (order to delivery from 5 weeks)	✓

Warranty

Up to 25 Year complete non pro-rated warranty	✓
10 Year Laminated glass warranty / 10 Year Insulated glass warranty	✓

Functionality

Child friendly	✓
Finger safe gaskets	✓
Low threshold (zero trip hazard)	✓
Easy to operate (effortlessly smooth)	✓
Slim flat handles (for reduced door stacking)	✓
Structurally strong (built to last)	✓
In-line system (inward & outward opening options, offering a practical functionality, to your living space & home)	✓

Customer Support

Total customer satisfaction	✓
Installation tutorials (online videos)	✓
Brochure request (web download)	✓
Brochure request (postal)	✓

Thermal Efficiency

Weather Proofing, ASTM and AAMA weather tested	✓
NFRC thermally tested	✓
Thermally Broken aluminum as standard	✓
Tested for water ingress and air infiltration	✓
High performance EPDM rubber seals and brush seals	✓
U Value from as low as 0.27 / 1.24	✓

Security

FSDC

Encapsulated running gear	✓
Hardened steel hook locks	✓
Dead bolts	✓
Top and bottom shoot bolts	✓
Keyed locks as standard	✓
Internally glazed	✓
Security hinges (none of which are face fixed to the door)	✓
Tongue and groove interlocking panels	✓

Locking

Keyed alike	★
Thumb turn	★
Emergency exit push bar OR Emergency exit push pad	★

Specification overview

Certification:

Florida Building Code Approved (FL16291)	✓
NFRC Approved	✓
AAMA Certified	✓



International certifications

CE Compliant BS EN 14351-1: 2006 (thermal, water tightness, wind resistance, air permeability)	✓
Trustmark (Government endorsed standards, Quality of work, trading practices and customer satisfaction)	✓
FairTrades (symbolizes peace of mind for the customer as well as taking the worry out of finding a reputable business)	✓
The Guild Of Master Craftsmen (represents skill, integrity, quality and service)	✓
FENSA Registered (To ensure the Building Regulations & thermal performance standards are consistently maintained)	✓
UK Building Regulations (adhering to Part B, F, L, M, N)	✓
Secured By Design FD72 (Nationally recognized police initiative scheme, PAS023 wind & water, PAS024 security)	✓
ISO 9001:2008 (Quality Management Systems)	✓



Environmental

FSC Certified Hardwood timber (Environmentally sourced from sustainable forests)	✓
Recycled aluminum	✓
Recycled UPVC/vinyl	✓
Recycled timber (converted to briquettes and used to heat the factory)	✓
Waste Management System	✓

Materials - product overview

Wood (2 3/4" / 70mm), engineered hardwood for strength & integrity)	✓
Aluminum (1 3/4" / 45mm) Internal or external use	✓
Aluminum (2 3/4" / 70mm) External Doors	✓
Wood Clad Aluminum (2 3/4" / 70mm), Aluminum/Timber)	✓
Aluminum (2 3/4" / 70mm) Hurricane Doors	✓
Vinyl (2 3/4" / 70mm)	✓

Configurations - Over 130 Door opening options available

Inward Opening (In Swing)	✱
Outward Opening (Out Swing)	✱
Left folding/stacking	✱
Right folding/stacking	✱
Left/Right folding/stacking both ways	✱

Specification overview

Glass

Standard IG glass units (standard)	✓
Triple-paned glass units (optional)	✱
Low-E coated glass (optional)	✱
Tempered glass (standard)	✓
Laminated glass (optional)	✱
Impact Glass (optional)	✱
Internally glazed/beaded (standard)	✓
Super Spacer (optional)	✱
Argon gas filled (optional)	✱

Tracks & Rollers

In-line out of site track system	✓
Flush track as standard	✓
Sill option track	✱
Concealed running gear	✓
Top & Bottom rollers to distribute weight load	✓
Steel wheels (sealed bearings for maintenance free use)	✓

FINISHES & COATINGS - Wood;

FSC Certified hardwood timber (from sustainable managed forests)	✓
Eucalyptus, Meranti (mahogany) options	✱
European Oak (hardwood) option	✱
Anti-rot treated as standard	✓
Anti-fungal treated as standard	✓
Laminated, spliced, glued & pressure treated as standard	✓
Natural stain, factory sprayed 3 coats at 250 microns per coat (color match available)	✓
Low maintenance, life span of up to 10 years before they require maintenance	✓

FINISHES & COATINGS - Aluminum;

Powder coated, RAL colors (choice of custom color, color match available)	✱
Maintenance free, life expectancy of up to 25 years	✓

FINISHES & COATINGS - UPVC / Vinyl;

Aluminum reinforced EURO Matrix profile as standard	✓
Maintenance free, life expectancy of up to 25 years	✓

Hardware I - Lever handle

Ergonomically designed to fit all major modern door bolt locking systems	3 5/8" / 92mm Centers
Non-handed allowing use as either a left or right hand handle	supplied with spring cassette
Color/finish option available in:	White / Black / Gold / Chrome / Satin Nickel
Supplied with spindles and 2 sets of screws	to suit profiles 2 9/32" / 58mm - 2 3/4" / 70mm

Technical Information;

Corrosion resistance	BS EN 1670 - grade 5 (500 Hrs Salt Spray)
Handle/Backplate	Zinc Alloy BS1004A or Aluminum A360
Spindle:	Steel C1008, Zinc plated and yellow passivated
Powder Coating (minimum thickness):	White and Black (60 microns)
PVD/Chrome Coating (multiple layer plating process):	Gold / Chrome / Satin Nickel

Specification overview

HARDWARE II - Flat handle

Ergonomically engineered to fit all major modern door bolt locking systems	✓
Non-handed allowing them to be used as either a left or right hand handle	✓
Colour/finish option available in:	White / Black / Gold / Chrome / Satin Nickel / Stainless
Supplied with spindles and 2 sets of screws	✓
<i>Technical Information;</i>	
Corrosion resistance:	BS EN 1670 - grade 5 (500 Hrs Salt Spray)
Handle/Backplate:	Zinc Alloy BS1004A or aluminium A360
Spindle:	Steel C1008, Zinc plated and yellow passivated
Powder Coating (minimum thickness):	White and Black (60 microns)
PVD/Chrome Coating (multiple layer plating process):	Gold / Chrome / Satin Nickel

HARDWARE III - Pull handle

Material;	Aluminium Alloy
<i>Technical Information;</i>	
Powder Coating (minimum thickness):	White and Black (60 microns)
PVD/Chrome Coating (multiple layer plating process):	Satin Nickel

HARDWARE IV - Butt hinges

Heavy duty security folding door butt hinges	✓
Security:	provided via the secret grub screw (non visible)
Colour/finish option available in;	White / Black / Satin Nickel
<i>Technical Information;</i>	
Hinge Body:	Zinc Alloy BS1004A
Top/Bottom Bush:	Nylon 6
Pins Stainless Steel:	Steel C1008, Zinc plated and yellow passivated
Powder Coating (minimum thickness):	White and Black (60 microns)
PVD/Chrome Coating (multiple layer plating process):	Satin Nickel

HARDWARE V - Roller

Aesthetically pleasing and durable Roller System	✓
Ergonomically designed heavy duty roller system	Steel wheels
Sealed bearings, durable and stable construction	✓
Fully adjustable for optimum performance	✓
Colour/finish option available in:	White / Black / Satin Nickel / Stainless Steel
<i>Technical Information;</i>	
Corrosion resistance:	BS EN 1670 - grade 5 (500 Hrs Salt Spray)
Roller Shaft/Carrier:	Aluminium A360
Roller Wheels/Carriage:	Steel / Stainless Steel
Powder Coating (minimum thickness):	White and Black (60 microns)

Key

- Available (standard) ✓
- Choice / optional ✪
- Not available ✕



All information correct at time of going to print, December 2016

2 3/4" (70mm) Thermally Separated Aluminium

Ultimate performance. Hurricane & non impact rated

HD82

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Aluminium
Color Range:	Any RAL, matching available
U Factor / U Value (W/m2k) complete unit:	0.25 - 0.32 / 1.42 - 1.83
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1 1/8" / 28mm double glazed, low-E





2 3/4" (70mm) Thermally Separated Aluminium

Modern, strong and extremely durable.

AA72

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Aluminium
Color Range:	Any RAL, matching available
U Factor / U Value (W/m2k) complete unit:	0.25 - 0.32 / 1.42 - 1.83
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1 1/8" / 28mm double glazed, low-E




2 3/4" (70mm) Thermally Separated Aluminium

Ultimate Security performance. Tested for security integrity

Q72

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Aluminium
Color Range:	Any RAL, matching available
U Factor / U Value (W/m2k) complete unit:	0.25 - 0.32 / 1.42 - 1.83
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1 1/8" / 28mm double glazed, low-E




2 3/4" (70mm) Thermally Separated Aluminium

A modern look coupled with strength and durability

AA65

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Aluminium
Color Range:	Any RAL, matching available
U Factor / U Value (W/m2k) complete unit:	0.25 - 0.32 / 1.42 - 1.83
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1 1/8" / 28mm double glazed, low-E




1 3/4" (45mm) Non Thermal Aluminium

Slim sight lines and a smaller stacking space

NT45

Frame Width:	2 3/8" / 60mm
Frame Thickness:	1 3/4" / 45mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	10' / 3000mm
Panel Height Range (Min - Max):	1' / 305mm - 10' / 3000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Aluminium
Color Range:	Any RAL, matching available
U Factor / U Value (W/m2k) complete unit:	N/A
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1" / 24mm double glazed, low-E



2¾" (68mm) Engineered Wood


A modern look coupled with strength and durability

Frame Width:	2¾" / 68mm
Frame Thickness:	2¾" / 68mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Laminated Wood*
Color Range:	Any RAL, stain or unfinished
U Factor / U Value (W/m2k) complete unit:	0.19 - 0.28 / 1.09 - 1.59
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1½" / 28mm double glazed, low-E

*European Oak or Eucalyptus



EW68




2 3/4" (70mm) Aluminium Re-enforced Wood

Re-enforcement achieves improved strength & stability

RW65

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Wood / Aluminium
Color Range:	Any RAL, stain or unfinished
U Factor / U Value (W/m2k) complete unit:	0.19 - 0.28 / 1.09 - 1.59
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1 1/8" / 28mm double glazed, low-E




2 3/4" (70mm) Thermal Aluminium & Wood

Aluminium & Wood. The best of both worlds.

AW73

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Wood / Aluminium
Color Range:	Any RAL, stain or unfinished
U Factor / U Value (W/m2k) complete unit:	0.26 - 0.30 / 1.52 - 1.81
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1 1/8" / 28mm double glazed, low-E




2 3/4" (70mm) Thermal Aluminium & Wood

Aluminium & Wood. The best of both worlds.

AW65

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Wood / Aluminium
Color Range:	Any RAL, stain or unfinished
U Factor / U Value (W/m2k) complete unit:	0.26 - 0.30 / 1.52 - 1.81
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1 1/8" / 28mm double glazed, low-E




2 3/4" (70mm) PVCu / Vinyl

Strength and having fantastic thermal values

PV71

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	30' / 9000mm
Maximum Opening Height:	9' / 2700mm
Panel Height Range (Min - Max):	1' / 305mm - 9' / 2700mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	PVCu / Vinyl
Color Range:	White PVCu & Golden Oak, Rosewood VEKA Foils
U Factor / U Value (W/m2k) complete unit:	0.21 - 0.31 / 1.24 - 1.77
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	1 1/8" / 28mm double glazed, low-E




2 3/4" (70mm) Thermal Aluminium & GlassIIEdge™

Flush glazed, frameless glass system with aluminium.

AG75

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Glass outer / Aluminium inner
Color Range:	Glass tint or clear / RAL colour
U Factor / U Value (W/m2k) complete unit:	0.24 - 0.30 / 1.39 - 1.79
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	2" / 52mm triple glazed, low-E




2 3/4" (70mm) Thermal Aluminium & GlassIIEdge™

Flush glazed, frameless glass system with aluminium.

AG65

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Glass outer / Aluminium inner
Color Range:	Glass tint or clear / RAL colour
U Factor / U Value (W/m2k) complete unit:	0.24 - 0.30 / 1.39 - 1.79
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	2" / 52mm triple glazed, low-E





2 3/4" (70mm) Wood & GlassIIEdge™

Flush glazed, frameless glass system with wood.

WG65

Frame Width:	2 3/8" / 60mm
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Glass / Aluminium / Wood inner
Color Range:	Glass tint or clear / RAL colour, Stain, Unfinished
U Factor / U Value (W/m2k) complete unit:	0.24 - 0.30 / 1.39 - 1.79
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	2" / 52mm triple glazed, low-E






2 3/4" (70mm) GlassEdge™

Flush glazed, frameless glass to edge system

GG65

Frame Width:	N/A
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	Glass / Aluminium / Glass
Color Range:	Glass tint or clear / RAL colour
U Factor / U Value (W/m2k) complete unit:	0.24 - 0.30 / 1.39 - 1.79
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	2 3/4" / 52mm triple glazed, low-E



2 3/4" (70mm) Solid Movable Wall

Folding, Sliding & Stacking Movable Walls

MW65

Frame Width:	N/A
Frame Thickness:	2 3/4" / 70mm
Maximum Opening Width:	60' / 18300mm
Maximum Opening Height:	13' / 4000mm
Panel Height Range (Min - Max):	1' / 305mm - 13' / 4000mm
Panel Width Range (Min - Max):	1' / 305mm - 7' / 2100mm
Material:	TBD / Aluminium / TBD
Color Range:	TBD
U Factor / U Value (W/m2k) complete unit:	N/A
Guarantee (Product):	up to 25 years
Guarantee (Manufacturers):	10 years
Aluminum Thickness:	1/16" / 1.75mm
Glass units, standard (optional):	N/A

