

# DF2SL Heatflow

## Wireless controlled wall-mounted downflow fan heater with thermostat

The new Consort DF2SL Heatflow is a downflow fan heater with a variable thermostat. It features heating control options with compatible wireless controllers, comfort and setback temperature settings and automatic overheat safety cut-out. It provides rapid warmth and an adjustable heat output (1kW or 2kW) at installation.



fast warm-ups  
with 2kW output



variable  
thermostat



compatible with  
Consort's wireless  
controllers

### Features

- Up to 2kW heat output for fast heating
- Variable thermostat
- Compatible with advanced single zone controllers\* and SL controllers\*\*
- Automatic safety cut-out
- Double insulated class II appliance
- LED indicator light
- Finished in white

### Technical Specifications

- Heating capacity: 1kW, 2kW (depending on pre-setting)
- Supply voltage: 230V-240V, 50Hz
- Dimensions (W x H x D): 257 x 244 x 124 mm
- Weight: 1.5 kg



Note: Wireless controllers to be purchased separately.

\* Advanced single zone controllers: CRXSL and LC controllers

\*\* SL controllers: SLPBWIFI, SLPB, SLVT, SLVTB, SLPBWP controllers



Our wide range of wireless controllers are compatible with the DF2SL fan heater. The wireless controllers provide a longer heating period for your home or work area.



The DF2SL Heatflow fan heaters are sleek and compact, making them ideal for bathrooms, kitchens and areas requiring localised, controllable heat.